

	COUNTER SINK.
	TZ LOG BEAM.
	— 1" ALL-THREAD.
	— 1/4" STEEL PLATE, 7" DIAMETER, DRILLED 1-1/4" THROUGH CENTER TO ALLOW FOR ADJUSTMENT OF SETTLING NUT.
	POST DETAIL SCALE: 1" = 1'-0" 1
	30ALE. I - I-U
	— LOG JAB CHINKING.
\leq	
	DRILL BIT. PINS WILL THEN BE PLACED EVERY 8' THE DISTANCE OF THE LOG AND WITHIN 12" OF
	A BUTT JOINT.
)	— 1/2" x 5" INSULATION.
XR	
	— TOP LOG SADDLE NOTCHED TO FIT LOWER LOG.
	LOG CORNER DETAIL SCALE: 1" = 1'-0" 2
,	
	— 1/2" ALL-THREAD. LOG WILL BE DRILLED W/3/4" BIT @EACH ANCHOR BOLT.
	— 1/2" x 6" ANCHOR BOLT. — SILL SEAL ABOVE AND BELOW PRESSURE
	TREATED PLATE.
	— 2" x 6" PRESSURE TREATED SILL PLATE.
	— 4" 3000# CONCRETE.
	— #3 REBAR GRID. 2' O.C. TYP. FOR ALL CONCRETE FLOORS.
	— 8" x 8" x 16" C.M.U. BLOCK GROUTED
	EVERY CORNER AND 4' O.C. WITH
	EVERY 4TH ROW AND TOP BLOCK BEING BOND BEAM AND GROUTED
	CONT. — 2 - #4 REBAR CONT. W/ MIN. 18"
	OVERLAP.
	LOG, FOOTING DETAIL 3
	SCALE: 1" = 1'-0" 3